



VIDAR 2.0 Series
Thermal Imaging

Thermal Imaging Scope Vidar335 2.0

Technical Specifications



ThermTec Technology Co., Ltd.
Email: info@thermeyertec.com
Website: <https://www.thermeyertec.com>

VIDAR 335 2.0

Key Features

- Video recording, and snapshot, built-in memory chip up to 64GB.
- 384*288 thermal resolution, NETD less than 18mK.
- Two batteries enter to unprecedented 18-hour.
- A newly added shutter facilitates fast calibration.
- 1x--4x smooth or rapid zooming improves various experiences.
- Offer 5 different reticle colors to meet users' needs for visibility and contrast in various environments.
- Cutting-edge trajectory technology achieves even precise shooting at any distance.
- 1024*768 resolution with 0.39-inch OLED display.
- Picture in picture & RAV function.
- Polarity reversal for crosshairs.
- More APP-based features and extensions.

Applications

- Night hunting
- Observation

Specifications



Model	Vidar335 2.0
Microbolometer	
Type	Uncooled
Resolution	384x288
Pixel pitch	12μm
NETD	≤18mK
Spectral range	8-14μm
Frame rate	50HZ
Detection Range	1800m
Optics	
Objective lens	35mm, F1.0
Field of view	7.5°x5.6°
m@100m	13.2x9.9
Magnification	3.2X
Digital zoom	1.0-4.0X smooth & rapid zoom
Eye relief	45mm
Exit pupil	6mm
Diopter	±5D
Aiming Reticle	
Reticle	7
Reticle color	5, Black. white, red, green, blue
Display	
Type	AMOLED
Resolution	1024x768
Display size	0.39 inch
Color palette	6

Function	
Max. recoil power on rifled weapon	6000J
RAV	Yes
Audio Recording	Yes
Auto zeroing	Yes
Manual zeroing	Yes
Zeroing profiles	5
Freeze Zeroing	Yes
Picture-in-picture	Yes
Image calibration	Manual/Auto
Video Recorder	
Phone/video playback	Yes
Inbuilt memory	64GB
Interface	
Magnetic interface	Data transfer
Hotspot	Yes
Battery	
Battery type	Replaceable, 2*18650
Battery life	18h
Environment	
Operating temperature	-20- +50°C
IP rating	IP67
Weight, g	566
Size, mm	188*92.2*72
Accessories	
External cable	Magnetic interface data cable
Other accessory	Standard Picatinny rail, eyeshade, charger and etc.

Accessories




Picatinny rail(X1)



Allen key(X1)



Small allen key(X1)



Lithium battery(X4)



T2.9 Screw(X3)



Eyepiece hood(X1)



Magnetic charging wire(X1)



Charger(X1)



Lens cloth(X1)

Dimension

Unit: mm

